

AGRICULTURAL MACHINERY

**sitrex**<sup>®</sup>

# BASKET RAKE

**BR2030-6 / BR2030-7**



# BASKET RAKE



The Basket Rake BR2030 rakes cleanly and efficiently using quick and easy controls. Farmers who want to produce high quality hay find in this type of rake the right machine, ideal for their needs. After the passage of the basket rake the hay forms a clean swath since the teeth of the basket rake pass on the stubble leaving behind all the impurities. On the field no hay remains behind because the baskets float broadly and are transported on a tandem axle. The operator can control all the rake functions from the electro-hydraulic control panel. The system is easy to use because the buttons are identified by colors and the use is therefore very intuitive. You can make adjustments very quickly and easily during work. The operator can change the speed of the basket from the control panel and adjust the rake according to his needs and working conditions.

MODEL	BR2030 - 6 BARS	BR2030 - 7 BARS
Overall height [m (ft)]	2.0 (6'6")	2.0 (6'6")
Transport width [m (ft)]	3.2 (10'5")	3.2 (10'5")
Transport length [m (ft)]	7.8 (25'6")	7.8 (25'6")
Weight [kg (Lbs)]	2800 (6167)	2860 (6300)
Maximum working width [m (ft)]	9.2 (30')	9.2 (30')
Number of tines	444 total 37 tines per bar	518 total 37 tines per bar
Basket speed [rpm]	Variable: 60 ÷ 80 rpm	Variable: 60 ÷ 80
Operating speed [km/h (mph)]	3 ÷ 16 (2 ÷ 10)	3 ÷ 16 (2 ÷ 10)
Transport speed max [km/h (mph)]	32 (20)	32 (20)
Wheels	Tandem	Tandem
Tires	235/75-R15	235/75-R15
Electrical requirement	12V DC 7 pin connector	12V DC 7 pin connector
Hydraulic requirement	2 outlets 44 l/min (12 US gpm)	2 outlets 44 l/min (12 US gpm)
Maximum hydraulic pressure [ kPa (psi)]	17000 (2450)	17000 (2450)

Designs, materials and/or specifications are subject to change without notice and without liability thereof.

